



SIZES AND SPECIFICATIONS

Available

Tire Size	Stock Number	Tread Depth (1/32")	Inflated Overall Dia. (in.)	Dimensions Overall Width (in.)	Approved Rim (measuring rim) Width (in.)	Maximum Load Press. (lbs) (psi)	Revs Per Mile
33x13.50R15LT C 109Q	200-650	21.0	33.07	13.94	8.5-(11.0)	2270@35	628
35x14.50R15LT C 116P	200-580	21.0	34.80	14.57	10.0-(12.0)	2755@35	596
38x15.50R15LT C 123P	200-630	21.0	37.64	15.55	11.0-(12.0)-13.0	3415@35	551
LT305/70R16 E 124/121P	201-040	19.7	33.07	12.01	8.0-(9.0)-9.5	3525@65	628
LT315/75R16 E 127/124P	201-050	20.7	34.96	12.87	8.0-(8.5)-11.0	3860@65	594
LT385/70R16 D 130Q	201-060	21.0	37.72	15.35	9.5-(11.0)-12.0	4190@50	550
33x12.50R17LT E 120Q	200-760	21.0	32.95	12.68	8.5-(10.0)-11.0	3085@65	630
35x12.50R17LT E 125P	200-670	21.0	34.84	13.19	8.5-(10.0)-11.0	3640@65	596
37x13.50R17LT E 131P	200-600	21.0	37.05	14.27	8.5-(11.0)	4300@65	560
40x13.50R17LT D 131Q	200-770	21.0	39.72	14.57	8.5-(11.0)	4300@50	522
33x12.50R18LT E 118Q	200-690	21.0	32.95	12.68	8.5-(10.0)-11.0	2910@65	630
35x12.50R18LT E 123Q	200-550	21.0	35.04	13.39	8.5-(10.0)-11.0	3415@65	592
37x13.50R18LT D 124P	200-660	21.0	37.05	14.17	8.5-(11.0)	3525@50	560
38x15.50R18LT D 128Q	200-500	21.0	37.72	16.30	11.0-(12.0)-13.0	3970@50	551
33x12.50R20LT E 114Q	200-680	21.0	32.95	12.80	8.5-(10.0)-11.0	2600@65	630
35x12.50R20LT E 121Q	200-570	21.0	35.04	12.20	8.5-(10.0)-11.0	3195@65	592
37x13.50R20LT D 127Q	200-540	21.0	37.05	14.13	8.5-(11.0)	3860@65	560
38x15.50R20LT D 125Q	200-510	21.0	37.72	14.65	11.0-(12.0)-13.0	3640@50	550
40x15.50R20LT D 130Q	200-720	21.0	39.72	15.91	11.0-(12.0)-13.0	4190@50	522
37x13.50R22LT E 123Q	200-530	21.0	37.05	14.13	8.5-(11.0)	3415@65	560
40x15.50R22LT D 127Q	200-520	21.0	39.72	14.65	11.0-(12.0)-13.0	3860@50	522

* - Indicates Extra Load (XL)

All technical information subject to change without notice.

Passenger Tires used on Light Trucks & SUVs have reduced load capacities that differ from the maximum load listed. Diameter and width measurements are averages based on tires measured on specified measuring rim widths.

PRINT | CLOSE WINDOW